

# **HA130 RTJ PRO**

















## **OUTSTANDING ROUGH** TERRAIN DRIVING **CAPABILITIES**

- > Differential wheel lock: 4 wheel drive and steer, oscillating axle
- > Up to 4 simultaneous, proportional movements
- > Tightest turning radius on the market
- > Continuous outreach control

### **OPTIMIZED SERVICEABILITY**

- > Modular platform, quick and easy to repair
- > Easy access to all components
- > Self-diagnosis integrated to the lower control box

#### **RELIABLE SAFETY**

> Haulotte Activ'Shield Bar 2.0






# **HA130 RTJ PRO**

## **ROUGH TERRAIN** ARTICULATING BOOMS

TECHNICAL DATA	HA <mark>130</mark> RTJ PRO 4WD/4WS
Working height	136 ft 2 in
Platform height	129 ft 7 in
Horizontal outreach	65 ft 11 in
Up and over height	57 ft 5 in
Below ground reach	4 ft 11 in
Lift capacity	500 lb (2 pers.)
🗗 x 🕝 Platform size	8 ft x 3 ft
<b>(1)</b> Length	43 ft
A Length - transport	36 ft 1 in
<b>B</b> Width	8 ft 2 in
Width - with extended axles	10 ft 10 in
C Height - stowed	9 ft 10 in
Height - transport	12 ft 3 in
Vertical jib rotation	140° (+ 70° / - 70°)
Platform rotation	180° (+ 90° / - 90°)
Turntable rotation	360° continuous
Tailswing	12 ft 9 in
<b>D</b> Wheelbase	11 ft 6 in
■ Ground clearance	15 in
Tilt alarm	4 °
Maximum wind speed rating	28 mph
Gradeability	40 %
Outside turning radius - extended ax	kle 18 ft 10 in
Tires	445 / 65 - 22.5
Engine	Deutz, 55 kW, Tier 4




Weight

### **STANDARD** EQUIPMENT

- > Haulotte Activ'Shield Bar 2.0
- > Universal telematics plug
- > 4 wheel drive and 4 wheel steer
- > Front oscillating axle
- > 2 extendable axles
- > Fully proportional controls
- > 4 simultaneous movements
- > Differential wheel lock
- > Upper control box protection cover and tool tray in ultra-rugged composite
- > Modular large platform with swing door entry gate
- > Basket compensation ± 10°
- > AC power to the platform
- > Swing out engine tray
- > Tilt / load alarm and light
- > Flashing beacon
- > Travel alarm
- > Electric pump system and emergency descent controls in upper control box
- > 12 V battery
- > Engine pre-heater with light indicator
- > Low fuel level indicator (upper control box)
- > Towing hooks
- > Hydrostatic transmission

#### **OPTIONS** AND ACCESSORIES

- > Air line to platform
- > Lateral swing door entry gate (standard on US machines)
- > On-board hydraulic 3.7 kW generator
- > Biodegradable hydraulic oil
- > Hydraulic oil cooler
- > Cap with key for diesel tank
- > Hydraulic oil in tank and circuit for warm countries
- > Cold weather kit
- > Pipe cradle
- > Glazier kit
- > Automatic overspeed air shutdown valve (electric one-way valve, flame arrestor, spark arrestor)
- > 55W platform worklight



52,700 lb