

HT132 RTJ PRO

















OUTSTANDING ROUGH TERRAIN DRIVING FEATURES

- > Differential wheel lock
- > Up to 4 simultaneous, proportional movements
- > Dual load capacity
- > 3D jib

OPTIMIZED SERVICEABILITY

- > Self-diagnosis tool integrated in the lower control box
- > Fully modular basket for quick and easy repairs
- > Easy access to all components

INCREASED SAFETY

- > Haulotte Activ'Shield Bar 2.0 (standard in North America)
- > Smooth and precise controls
- > Strong, quick, and maneuverable boom




WWW.AERIALTITANS.COM

HT132 RTJ PRO

ROUGH TERRAIN TELESCOPIC BOOMS

TECHNICAL DATA

	HT132 RTJ PRO
Working height	138 ft 5 in
Platform height	131 ft 11 in
Horizontal outreach	66 ft 3 in
Lift capacity	500 lb (2 pers.) - 990 lb (3 pers.)
🗗 x 🕒 Platform size	8 ft x 3 ft
H Length - stowed	48 ft 7 in
A Length - transport	40 ft 4 in
B Width	8 ft 2 in
Width - with extended axles	10 ft 10 in
C Height - stowed	10 ft
Height - transport	10 ft
Vertical jib rotation	140° (+ 70° / - 70°)
Horizontal jib rotation	150° (+ 75° / - 75°)
Platform rotation	180° (+ 90° / - 90°)
Turret swing	360° continuous
Tailswing	9 ft 2 in
Wheelbase	11 ft 6 in
■ Ground clearance	15 in
Tilt alarm	3 °
Drive speed	0.2 - 3.1 mph
Maximum wind speed rating	28 mph
Gradeability	40 %
Turning radius - outside	18 ft 10 in
Tires	445 / 65 - 22.5
Engine	Deutz, 55 kW, Tier 4
Weight	47,187 lb





STANDARD EQUIPMENT

- > Haulotte Activ'Shield Bar (standard in North America)
- > 4 wheel drive and 4 wheel steer
- > Front oscillating axle
- 2 extendable axles
- Fully proportional controls
- > 4 simultaneous movements
- > Differential wheel lock
- > Upper control box protection cover and tool tray in plastic ultra-solid material
- > Dual load capacity 500 lbs (2 persons) 990 lbs (3 persons)
- > Standard modular large platform with swing door entry gate
- > Basket compensation ± 10°
- > AC power to the platform 110 / 220 V
- Swing out engine tray
- > Tilt / load alarm and light
- > Flashing drive beacon
- > Travel alarm
- > Hourmeter
- > Electric pump system and emergency descent
- > 12 V battery / electrical control system
- > Engine pre-heater with light indicator
- > Low fuel level indicator (upper control box)
- Towing hooks
- > 3D jib

OPTIONS AND ACCESSORIES

- > Air line to the platform
- > Lateral swing door entry gate (Standard on US machines)
- > On-board hydraulic generator
- > Biodegradable hydraulic oil
- > Hydraulic oil cooler
- > Hydraulic oil in tank and circuit for warm countries
- > Cap with key for diesel tank
- > Glazier pack
- > Cold weather kit
- > Pipe cradle
- > Automatic overspeed air shutdown valve (electric one-way valve, flame arrestor, spark arrestor)
- > Worklight

